



MS31

MICROWAVE TOUCHLESS ACTUATOR WITH ADJUSTABLE RANGE AND RELAY HOLD TIME

DESCRIPTION

BEA's **MAGIC SWITCH® Family** utilizes proven microwave motion technology to ensure consistent, dependable touchless activation and can be adjusted to comply with the ANSI 156.10 knowing act standard.

The **MS31** detects moving objects such as a hand, cart or wheelchair and reduces touchpoints in high traffic areas commonly found in shopping and transportation centers. Applications requiring hygienic activation include hospitals, pharmacies, clean rooms and foodservice facilities.


APPLICATIONS




Full Energy Swing Doors



Low Energy Swing Doors



Industrial Doors







Healthcare Environments



TECHNICAL SPECIFICATIONS

Technology	Microwave Doppler Radar
Radiated Frequency	24.125 GHz
Radiated Power Density	< 5 mW / cm ²
Detection Mode	Motion (bidirectional)
Detection Range	4 – 24" (adjustable)
Output	Relay with switch-over contact (voltage-free)
Max. Contact Voltage	60 VDC / 125 VAC
Max. Contact Current	1 A (resistive)
Max. Switching Power	30 W (DC) / 60 VA (AC)
Output Hold Time	0.5 – 30 s
Supply Frequency	50 – 60 Hz
Supply Voltage*	12 – 24 VAC ±10%, 12 – 24 VDC +30% / -10%
Power Consumption	< 1.5 W
Weight	0.34 lbs
Material	PC, PE
Temperature Range	-4 – 131 °F (-20 – 55 °C)
IP Rating	IP54
Dimensions	
Jamb Plate	4 ½" (H) × 1 ¾" (W) × ¼" (T)
Single Gang	4 ½" (H) × 2 ¾" (W) × ¼" (T)
Double Gang	4 ½" (H) × 4 ½" (W) × ¼" (T)
Round Plate	6" (D) × ¼" (T)
Certification	EMC: 2004 / 108 / EC FCC: G9B-210161 IC: 4680A-210161



DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company